Wired Economical Digital Camera Tracking & Discussing Conference System

Chairman & Delegate Units

Model: VCS-HR632Gi-C & VCS-HR632Gi-D (With Speaker) (DIN-8P or RJ45)



SUMMARY

• This is a new intelligent wired economical digital camera tracking & discussing conference system, which perfectly introduces all digital technology and integrated network technology into the conference system, and fully combines advanced digital technology, network technology and audio technology. It can be seamlessly connected with intelligent central control system, video conference system, providing a more complete solution for efficient modern conference system engineering.

FEATURES

- Fashionable patented design, adopting alloy bottom shell combined with high-performance ABS surface shell, the overall high-grade solemn, in line with modern aesthetic standards
- The unit is powered by the system host. The input voltage is 24V, which is a safe range.
- Unit with 8-core wire interface adopts T-type 8-core connection, and the wire is shielded by full-line aluminum foil, which greatly reduces the interference of strong electromagnetic waves on the wire
- The unit of the network cable interface adopts super cat-6 network cables, "hand in hand" cable connection mode
- Professional high-fidelity capacitor microphone, sensitive pickup, clear voice, bandwidth up to 20Hz ~ 20KHz
- 6. Adopt anti-interference circuit design to prevent interference from electronic products such as mobile phones

- The microphone head has a two-color speaking light ring, the light ring is always red when the unit speaks, and the light ring is always green when the unit requests to speak.
- Mechanical switch design, the pattern is always bright green when standby, the pattern is always bright red after pressing, and also has color switching function
- 1.14-inch high-brightness IPS TFT display, the display content is clear, can display the unit parameters, date and time, speaking volume, monitoring volume, etc. that are being operated, and clearly understand the current using situation
- 10. Microphone with speaking timing function
- 11. The microphone unit has a speaker and a headphone output port with volume adjustment button, which can freely select the output mode and adjust its volume
- "Hand in hand" connection method, support hot plug, easy installation and maintenance
- The chairman unit has the function of approving the speech request of the delegate;
- 14. The chairman unit is not limited by the number of speakers;
- 15. The chairman unit has the priority function of controlling the order of the conference:
- 16. The connection position of the chairman unit is not restricted;
- 17. A system can support the use of multiple chairman units at the

1/3



Wired Economical Digital Camera Tracking & Discussing Conference System

Chairman & Delegate Units

Model: VCS-HR632Gi-C & VCS-HR632Gi-D (With Speaker) (DIN-8P or RJ45)

SPECIFICATIONS

Model No.	VCS-HR632Gi-C/D (With Speaker)	
Working Voltage	DC24V	
Cable	DIN-8P or RJ45	
Capsule	Cardioid	
Sensitivity	-46 dBV/Pa	
Frequency response	20Hz~20KHz	
Input impedance	2 kΩ	
Directional 0°/180°	> 20 dB (1 kHz)	
Equivalent noise	20 dBA (SPL)	
SPL	125 dB (THD<3%)	
S/N ratio	>80dB	
Cross talk	>80dB	
T.H.D	< 0.05%	
Display	1.14-inch IPS TFT	
Built in speaker	8Ω 2W	
Earphone load	>10 Ω	
Earphone volume	10 mW	
Earphone jack	3.5mm ×1	
Size (LxWxH)	Base: 105.6*146*49.5mm	
	Gooseneck Mic: 420mm	
Weight	Base: 0.56 kg	
	Gooseneck Mic: 0.07kg	
Colour	Black +Silver	
Installation	Desktop style	
Transport	-40°C to +70°C	
Operating	0°C to +45°C	
Max.relative humidity	< 95% (not condensing)	
-		

2/3



Wired Economical Digital Camera Tracking & Discussing Conference System

Chairman & Delegate Units

Model: VCS-HR632Gi-C & VCS-HR632Gi-D (With Speaker) (DIN-8P or RJ45)

DIMENSIONS (mm)







